Table of Contents

E83 Life Cycle Impulse Workbook

Subject	Page
Introduction	
Body Front Rear	
Interior	
Drivetrain N52 Engine Intake Air Duct Digital Engine Electronics (DME) 6-speed Manual Transmission 6-speed Automatic Transmission GM6 (6L45)	
Chassis	

Table of Contents

Subject

Page

8
8
8
8
8
8
8

Life Cycle Impulse Workbook

Model: E83

Production: from 8/2006

OBJECTIVES

After completion of this module you will be able to:

• Identify the changes made to the E83 X3 LCI

4

Introduction

The BMW X3 has been available on the market as of the 2004 model year and represents a premium product in the segment of compact luxury SUVs.

As of August 2006 production, the E83 will undergo a redesign in order to maintain its leading position in the market and to fend off the ever increasing number of competitors.

This model redesign, known as LCI (Life Cycle Impulse), includes a pronounced visual upgrade, the introduction of new engines as well as a whole series of improvements in details as well as in the range of interior trim and fittings.

As of September 2006, the E83 X3 3.0i with M54B30 (170 kW/231 bhp) will be replaced with the X3 3.0si with N52B3001 (191 kW/260 bhp).



Body

The only technical change is to the openings for the reversing lights in the inner panel of the rear hatch. Due to the higher positioning of these lights, it was also necessary to displace the clearance for their bulbs further upward.

The carrier, sheet metal components and assembly concept remain unchanged. Only the underbody paneling has been adapted to the new engines as part of the model redesign. Modifications to the bodyshell components are solely restricted to details such as the repositioning of threaded connections, pins or securing elements for the adapted wiring harnesses.

All parts of the bodyshell (hood/tailgate, side panels, doors, sills and weatherstrips) remain unchanged. The same also applies to the body connection points.

Front

The redesigned E83 can be immediately distinguished from its predecessor by the partly painted bumpers and the double kidney grill that extends further downward.





Front view - Left: E83 up to 8/06, Right: E83 LCI

The newly designed front bumper which was previously two-piece is now three pieces. A top section painted in the car color and a bottom cover that is also painted are now clipped onto the blackstructured, bolted carrier. These painted parts can be individually replaced as required by removing the complete bumper.

The kidney grills now extend further downward is available only with light titanium bars.

The grill between the double kidney and bumper as well as the lower grill are black on all vehicles.

Rear

The rear bumper on the E83 LCI is also a new design. It is now made up of four main parts (previously one-piece). Two black side panels and one exhaust finisher also in black are fitted on a carrier painted in the car color.

The panel at the lower edge of the rear hatch is now also painted in the car color, thus making a decisive contribution to the overall higher grade impression of the X3's rear end.

Two separate reflectors are clipped on to the left and right of the exhaust finisher.

The PDC sensors of the rear bumper are located in the painted area and are therefore painted in the car color (unchanged black at the front).

The inner panel of the rear hatch is adapted to the new design layout of the lights.

Although the exterior shape remains unchanged, different openings are required to accommodate the repositioning of the reversing lights.



Rear view - Left: E83 up to 8/06, Right: E83 LCI

E83 Life Cycle Impulse Workbook

Interior

Cockpit

The dashboard has been upgraded by numerous details. The instrument cluster shroud (previously attached) provides for a wider color separation groove and a more harmonious general impression. The dashboard, shroud, and airbag cover also have a new structure finish.

The cover of the glove compartment is positioned slightly lower.

The trim covers for the fresh air grills, the light switch cluster and the cup holder are now coated with soft paint (three different colors - depending on interior color).

Both the basic steering wheel as well as the sports steering wheel now feature a new steering wheel rim and a new cover.

In addition, the sports steering wheel features new spokes and a new backing. Both steering wheels have 3 spokes, the previous 4spoke basic steering wheel is no longer available.

As in other model series, the interior rear-view mirror in the E83 is available with a digital compass.

Door Panels

The door mirrors have also been distinctly upgraded by new surface structuring and geometry. The connection to the dashboard has been improved while the trim covers for the speakers are now larger due to the installation of new speakers.

Storage compartment shelves integrated in the door trim panel replace the previous netshell combination. The finisher for the power window switches are now smaller.



Door trim panel - Left: E83 up to 8/06, Right: E83 LCI



Cockpit - Left: E83 up to 8/06, Right: E83 LCI

Drivetrain

N52 Engine

The N52 engine first offered in the E90 will be reengineered for the September 2006 launch and will then be known as the N52K. The exact engine designation will N52B30O1.



Compared to the M54 6-cylinder engine previously fitted in the E83, the N52K is characterized by lower fuel consumption (12% reduction), reduced weight (10 kg less), 35 hp (30 kW) increase in power output and an increase of 11 lb ft torque.

The exhaust manifold has been slightly adapted to match the geometry of the E83.

The same also applies to the oil pan with modified underbody area and threaded connection to the front axle.

The shape of the engine support has been modified to accept the N52. The power steering oil reservoir is now mounted on the screw connection for the alternator instead of on the frame side member as previously.

Intake Air Duct

For the first time at BMW, the intake silencer is a fixed part in the engine. The unfiltered air duct is crash-optimized. An unfiltered air resonator and a time chamber filtered air resonator are used in order to satisfy acoustics requirements.

Digital Engine Electronics (DME)

The engine management MSV80 is used in connection with the N52K. This system is a further development of the MSV70 and has been adapted in terms of several details.

6-speed Manual Transmission

The synchromesh of the gearshift mechanism has been newly developed to provide outstanding gearshift comfort both at low as well as elevated shift forces.

1st/2nd gearshift now takes place in double cone synchromesh and single-cone synchromesh for 3rd/4th and 5th/6th gear.

A central selector valve connects the gearshift with a shift gate on the inside for the first time. Another new feature is the passive shift lock that guarantees distinctly greater locking reliability in addition to further optimized smoothness of operation.

6-speed Automatic Transmission GM6 (6L45)

The new automatic transmission GM6 replaces the previous transmission GM5 in the E83. The transmission has 6 forward drive ranges. The spread and gear ratio are virtually identical to the GM5. Its main advantages include a 6 % reduction in fuel consumption and improved gearshift dynamics.

The lower fuel consumption results from the use of neutral idle control (NIC), low converter slip thanks to the use of a turbine-tor-sion damper as well as reduced drag losses in the clutches.

In the GM6 is a one-way clutch to ensure stable shift quality when shifting from 1st to 2nd. Thanks to their high drive percentage with the clutch engaged, converters with turbine-torsion dampers provide a direct connection to the engine.

The transmission control unit is accommodated together with the hydraulic control unit in the transmission (mechatronics concept). This arrangement provides advantages in terms of package space and, due to the smaller number of interfaces, it also ensures increased system reliability.

Chassis

Various modifications to the chassis of the E83 have been necessary to accommodate the higher performance N52K engine. Most of these modifications, however, are restricted to geometric adaptations (steering system and heat shields).

DXC+

In addition to the known features such as ABS, ASC, CBC, DSC and HDC, the following will be added:

- Dynamic Traction Control (DTC) for ensuring maximum traction irrespective of the driving surface
- Hill starting assistance (Hill-holder)
- Dry brakes in rain
- Brake standby/brake travel reduction
- Brake fading assistance

RDC

All E83 vehicles will be equipped with the tire pressure monitoring system RDC which was introduced in March 2006.

Power Steering Cooling

The DSC control unit has an additional program module for the power steering cooling.

This function increases the fan speed to secure the required cooling capacity under high load conditions (e.g. uphill/downhill driving) at low speed. The signals relating to the driving speed, power output (via HFM) and steering angle lock are used as the control data for this purpose.

Electrical Systems

EWS 4.4

The E83 will be equipped with the EWS 4.4. This electronic control provides increased anti-theft protection, and eliminates the need for DME - EWS alignment.

Lights Module 2

The lights module 2 replaces the previous light switch cluster in the E83 LCI and combines the features of the AHL control unit.

Rear Seat Heating

Rear seat heating will be offered in all X3 models.

Oil Level Indicator

The oil level indicator is now integrated in the instrument cluster.

Radio, CD

The new radio platform of all E83 features a double tuner and station list expansion.

An AUX-In jack is provided on the center console for the connection of external audio sources.

The Random function in the CD changer now only refers to the selected CD and no longer to all (up to six) CDs in the magazine of the changer. This reduced number of selection options substantially shortens the pauses between the music tracks.

Navigation

The computer hardware is now lead-free and therefore recyclable.